

Regulator with ON/OFF

Monolithic IC MM3051□~MM3055□U

Outline

This IC is a low current consumption (1.5μA typ.), ultra-small CMOS regulator with ON/OFF control function. The ON/OFF control pin logic for MM3051H ~ MM3055F and MM3051T ~ MM3055R is reversed.

Features

- | | |
|----------------------------------------------|------------------------------------------------------------------------------|
| 1. I/O voltage difference (MM3054□~ MM3055□) | 25mV typ. ($I_o=1\text{mA}$) |
| 2. Current consumption | 1.5μA typ. ($V_{IN}=V_O+2\text{V}$) |
| 3. Output current | 80mA min. ($V_{IN}-V_{OUT}=2\text{V}$) |
| 4. Output voltage rank | 1.7~5.5V (0.1V step) |
| 5. Output ON/OFF control function | High: ON, Low: OFF (MM3051H~MM3055F)
High: OFF, Low: ON (MM3051T~MM3055R) |


Package

SC-82ABA
 SC-82ABB

Applications

1. Portable equipment
2. Cellular telephone, PHS
3. Cordless telephone
4. Other battery-powered portable equipment


Pin Assignment




The ON/OFF control pin logic for MM3051H ~ MM3055F and MM3051T ~ MM3055R is reversed

Equivalent Circuit Diagram

MM3051H ~ MM3055FU



MM3051T ~ MM3055RU



Pin Description

Pin No.	Pin name	Function			
1	GND	GND Pin			
2	V _{DD}	Voltage supply pin			
3	V _{OUT}	Regulator output voltage pin			
4	$\overline{\text{CE}}$ or CE	Output voltage ON/OFF-Control pin			
		MM3051T~MM3055R		MM3051H~MM3055F	
		$\overline{\text{CE}}$	Output	CE	Output
		L	ON	L	OFF
		H	OFF	H	ON
		Connect $\overline{\text{CE}}$ pin with GND pin, when it is not used.		Connect the CE pin to V _{DD} when not using it.	

Absolute Maximum Ratings (Except where noted otherwise, Ta=25°C)

Item	Symbol	Ratings	Units
Storage temperature	T _{STG}	-40~+125	°C
Operating temperature	T _{OPR}	-30~+85	°C
Supply voltage	V _{DD}	-0.3~+9	V
Output current	I _{OUT}	150	mA
Allowable loss	P _d	150 (Alone)	mW

Recommended Operating Conditions (Except where noted otherwise, Ta=25°C)

Item	Symbol	Ratings	Units
Operating temperature	T _{OP}	-30~+85	°C
Supply voltage	V _{OP}	V _{OUT} +0.3~8	V

Electrical Characteristics (Except where noted otherwise, Ta=25°C, V_{CE}=V_{IN})

MM3051H ~ MM3055FU

Item	Symbol	Measurement conditions	Min.	Typ.	Max.	Units
Supply current	I _{SS}	V _{IN} =V _{OUT} +2.0V, Excluding CE Pin Current (I _{CE})		1.5	3.0	μA
Supply current (OFF)	I _{standby}	V _{IN} =V _{OUT} +2.0V, V _{CE} =V _{IN}		0.1	1.0	μA
Line regulation	ΔV _{OUT} /ΔV _{IN}	I _{OUT} =1mA, V _{OUT} +0.5V ≤ V _{IN} ≤ 8V	0	0.05	0.20	%/V
Input voltage	V _{IN}				8.0	V
Vo temperature coefficient	ΔV _{OUT} /ΔV _{opt}	I _{OUT} =10mA -30°C ≤ T _{OPT} ≤ 85°C		±100		ppm/°C
Output short-circuit current	I _{lim}	V _{IN} =V _{OUT} +2.0V, V _{OUT} =0V		60		mA
CE pull down resistance	R _{PD}	V _{IN} =V _{OUT} +2.0V	1.5	4.0	12.0	MΩ
CE high threshold voltage	V _{CEH}	V _{IN} =V _{OUT} +2.0V	1.5			V
CE low threshold voltage	V _{CEL}	V _{IN} =V _{OUT} +2.0V			0.25	V

Note: V_{OUT} is the output voltage typ. value in the specifications.

Make sure that output current does not exceed loss tolerance.

MM3051T ~ MM3055RU (Except where noted otherwise, Ta=25°C, V_{CE}=GND)

Item	Symbol	Measurement conditions	Min.	Typ.	Max.	Units
Supply current	I _{SS}	V _{IN} =V _{OUT} +2.0V, Excluding CE Pin Current (I _{CE})		1.5	3.0	μA
Supply current (OFF)	I _{standby}	V _{IN} =V _{OUT} +2.0V, V _{CE} =V _{IN}		0.1	1.0	μA
Line regulation	ΔV _{OUT} /ΔV _{IN}	I _{OUT} =1mA, V _{OUT} +0.5V ≤ V _{IN} ≤ 8V	0	0.05	0.20	%/V
Input voltage	V _{IN}				8.0	V
Vo temperature coefficient	ΔV _{OUT} /ΔV _{opt}	I _{OUT} =10mA -30°C ≤ T _{OPT} ≤ 85°C		±100		ppm/°C
Output short-circuit current	I _{lim}	V _{IN} =V _{OUT} +2.0V, V _{OUT} =0V		60		mA
CE pull up resistance	R _{PU}	V _{IN} =V _{OUT} +2.0V	1.5	4.0	12.0	MΩ
CE high threshold voltage	V _{CEH}	V _{IN} =V _{OUT} +2.0V	1.5			V
CE low threshold voltage	V _{CEL}	V _{IN} =V _{OUT} +2.0V			0.25	V

Note: V_{OUT} is the output voltage typ. value in the specifications.

Make sure that output current does not exceed loss tolerance.

Electrical Characteristics 2

MM3051H ~ MM3055FU


[illegible]

Electrical Characteristics 3


MM3051T ~ MM3055RU

Product name	Item												
	Output voltage				Output current			Load regulation			Input-Output differential voltage		
	V _{OUT} (V)				I _{OUT} (mA)			ΔV _{OUT} /ΔI _{OUT} (mV)			V _{DIF} (mV)		
	Test condions	Min.	Typ.	Max.	Test condions	Min.	Typ.	Test condions	Typ.	Max.	Test condions	Typ.	Max.
MM3051T	V _{IN} -V _{OUT} =2.0V 10μA ≤ I _{OUT} ≤ 10mA	1.666	1.700	1.734	V _{IN} -V _{OUT} =2.0V	35		V _{IN} -V _{OUT} =2.0V 1mA ≤ I _{OUT} ≤ 35mA	30	45		60	90
MM3051U		1.764	1.800	1.836									
MM3051V		1.862	1.900	1.938									
MM3052L		1.960	2.000	2.040									
MM3052M		2.058	2.100	2.142									
MM3052N		2.156	2.200	2.244									
MM3052P		2.254	2.300	2.346									
MM3052Q		2.352	2.400	2.448									
MM3052R		2.450	2.500	2.550									
MM3052S		2.548	2.600	2.652									
MM3052T		2.646	2.700	2.754									
MM3052U		2.744	2.800	2.856									
MM3052V		2.842	2.900	2.958									
MM3053L		2.940	3.000	3.060									
MM3053M		3.038	3.100	3.162									
MM3053N		3.136	3.200	3.264									
MM3053P		3.234	3.300	3.366									
MM3053Q		3.332	3.400	3.468									
MM3053R		3.430	3.500	3.570									
MM3053S		3.528	3.600	3.672									
MM3053T		3.626	3.700	3.774									
MM3053U		3.724	3.800	3.876									
MM3053V		3.822	3.900	3.978									
MM3054L		3.920	4.000	4.080									
MM3054M		4.018	4.100	4.182									
MM3054N		4.116	4.200	4.284									
MM3054P		4.214	4.300	4.386									
MM3054Q		4.312	4.400	4.488									
MM3054R		4.410	4.500	4.590									
MM3054S		4.508	4.600	4.692									
MM3054T		4.606	4.700	4.794									
MM3054U		4.704	4.800	4.896									
MM3054V		4.802	4.900	4.998									
MM3055L		4.900	5.000	5.100									
MM3055M		4.998	5.100	5.202									
MM3055N		5.096	5.200	5.304									
MM3055P	5.194	5.300	5.406										
MM3055Q	5.292	5.400	5.508										
MM3055R	5.390	5.500	5.610										

Measuring Circuit




Typical Application Circuit




note: This regulator is not internally compensated and thus require an external output-capacitor (C_{OUT}) for stability.

Characteristics (3.0V product except where noted therwise, Ta=25°C)


Input-Output Differential Voltage




Line Regulation




Load Regulation




Supply Current




CE Pin Current VS CE Pin Voltage High Active




CE Pin Current VS CE Pin Voltage Low Active




Output Voltage VS Temperature



Input Current VS Temperature



Ripple Rejection



Allowable Loss

